WO 2005/104276 PCT/JP2005/006542

19 CLAIMS

1. An electrolyte layer for a fuel cell comprising:

a compact substrate through which passes a gas supplied to the electrochemical reaction;

a porous layer with fine pores that is formed on the substrate; and

an inorganic electrolyte supported in the pores.

2. An electrolyte layer for a fuel cell according to
 Claim 1, wherein

the substrate includes hydrogen-permeable, and the electrolyte includes proton-conducting.

- 15 3. An electrolyte layer for a fuel cell according to Claim 2, wherein the electrolyte includes a solid acid.
  - 4. An electrolyte layer for a fuel cell according to Claim 2, wherein the electrolyte includes a liquid acid.

5. A fuel cell comprising:

5

20

an electrolyte layer for a fuel cell according to any one of Claims 1 through 4, and

an electrode adjacent disposed adjacent to the porous layer, on the side opposite the substrate.

WO 2005/104276 PCT/JP2005/006542

20

6. A method of manufacturing an electrolyte layer for a fuel cell, the method comprising:

preparing a compact substrate through which passes a gas supplied to the electrochemical reaction;

forming a porous layer with fine pores on the substrate;

supporting an inorganic electrolyte in the pores.

- 7. A method of manufacturing an electrolyte layer for a

  10 fuel cell according to Claim 6, wherein
  the substrate includes hydrogen-permeable, and
  the electrolyte includes proton-conducting.
- 8. A method of manufacturing an electrolyte layer for a

  15 fuel cell according to Claim 7, wherein

  the electrolyte includes a solid acid, and

  the supporting the inorganic electrolyte includes

  introducing a solution of a solid acid into the pores of

  the porous layer, and
- 20 drying the porous element containing the solution.